



Touch Screen



Set programs



Pneumatic



Suitable for :

- Sports goods
- Advertising, flags, banners, accessories
- Large photos, posters
- Transfer on hard substrates (ceramic, aluminium, plastic, wood...)
- Textile : home finishing, apparel, curtains...
- Awning

- Ideal for sublimation with good productivity and flexibility
- Fast startup ! (15 to 20min)
- Plate in rectified high quality aluminium
- Perfect heat distribution (multiple heating zones)
- PT100 platinum heat sensor
- 2-year guarantee on the machine
- 10-year guarantee on heating elements
- Front load motorized double sliding plate
- Manufactured in France.

## OPTIONAL ACCESSORIES




Sublimation paper



Polyester Felt



Nomex® Cover



Teflon Cover



Air extractor



Compressor

Email

sales@sefa.fr  
 support@sefa.fr  
 www.sefa.fr

Phone

Office : + 33 4 68 74 05 89  
 Fax : + 33 4 68 74 24 08

Address

SEFA SAS  
 Z.I. PASTABRAC  
 11 260 ESPERAZA (FR)



## TECHNICAL CHARACTERISTICS

Type	Pneumatic
Operation	SLIDE - Tray with double automatic drawer
Platen size	SUBLI-1510+ : 1570x1070 mm SUBLI-1812+ : 1870x1270 mm SUBLIMAXI-2513 : 2550x1300 mm
Weight	SUBLI-1510+ : 1000 KG SUBLI-1812+ : 1394 KG SUBLIMAXI-2513 : 2180 KG
Max thickness	45 mm
°C / °F Max	220 °C / 429 °F
Power	SUBLI-1510+ : 20,25 KW / 32 A SUBLI-1812+ : 30,25 KW / 46 A SUBLIMAXI-2513 : 35 KW / 56 A
Power supply	400 V 3-phases
Applications	ChromaLuxe, sublimation rigid substrates, textile sublimation

## SETTINGS



Touch electronics developed by Sefa  
Precise and fast regulation (PID control)  
4 recordable programs  
Counter with reset  
Double timer  
Energy saving

From 0 to 600 s (precision +/- 1%).  
From 0 to 220°C (precision +/- 1%).

Heating time to reach 180°C : 15 min.


## OPTIONAL ACCESSORIES




**ASP-SUBLI**  
Exhaust system to evacuate sublimation fumes.



**COMP-XXX**  
Silent compressor  
COMP-111 : 50L. 111Lt/min.  
for SUBLI-1510+  
COMP-240 : 50L. 240Lt/min.  
for SUBLI-1812+  
COMP-300 : 150L. 300Lt/min.  
for SUBLIMAXI-2513




**FEU-XXX**  
Polyester felt for lower plate.  
FEU-022 (SUBLI-1510+)  
FEU-019 (SUBLI-1812+)  
FEU-025 (SUBLIMAXI-2513)



**TOI-T1510+ / T1812+ / T2513**  
Teflon cover for heating plate.



**TOI-N1510+ / N1812+ / N2513**  
Nomex® cover for heating plate.



**PAP-TP-SE64300 / SE44100**  
High quality sublimation paper available in 44"x30m and 64"x100m.

## DIMENSIONS

### SUBLI-1510+



### SUBLI-1812+



### SUBLIMAXI-2513



Box weight CAI-SUBLI : 327 kg  
Box weight CAI-SUBLI2513 : 432 kg